

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_N-50-7-69/133\_N



### Description

Straight cable plug

SUHNER full crimp cable attachment  
Water protection according to IP 67



### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 11 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0345 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	MVQ (Silicone Rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

#### Related Documents

Outline drawing DOU-00008098  
Assembly instruction DOC-0000311731

#### Ordering Information

Single package 11\_N-50-7-69/133\_NE

#### Additional Information

Suitable cables S\_07162\_B, LMR-400  
Interface standards IEC 61169-16\_MIL-STD-348A/304\_CECC 22210

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

**WAIVER!**  
It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**

Document: DOC-0000183790 O

Issued: 02.11.09

Uncontrolled Copy

Page 1/1



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com